

CLAMP-ON METERS

200, 400 & 600 SERIES
GENERAL PURPOSE METERS

MODELS 203/403/603 & 205/405/605

Users can be sure of working in a higher degree of safety with 1000V CAT IV rated meters (model dependent)



SPECIFICATIONS

MODELS	203/403/603 TRMS	205/405/605 TRMS
ELECTRICAL		
Current AC (rms)	600/1000/2000A	600/1000/2000A
Current DC	900/1500/3000A	900/1500/3000A
Current AC+DC	-	900/1500/3000A
Voltage AC (rms)	1000/1000/1000V	1000/1000/1000V
Voltage DC	1000/1000/1000V	1000/1000/1000V
Voltage AC+DC	-	1000/1000/1000V
Ohms	60/100/100k Ω	60/100/100k Ω
Continuity (Buzzer)	Yes (< 40 Ω)	Yes (< 40 Ω)
Diode Test	Yes	Yes
Total Harmonic Distortion	-	Yes
Single- and 3-Phase Real Power (AC, DC, AC/DC)*	-	600/1000/2000kW
Single- and 3-Phase Reactive Power (AC, DC, AC/DC)*	-	600/1000/2000kvar
Single- and 3-Phase Apparent Power (AC, DC, AC/DC)*	-	600/1000/2000kVA
Temperature (int., ext., C°, F°)	Yes	-
Voltage Frequency (Hz)	20kHz	20kHz
Current Frequency (Hz)	3/2/1kHz	3/2/1kHz
Power Function (W, var, VA)	-	Yes
Power Factor	-	Yes
THD-r/THD-f	-	Yes
Adapter (AC/DC)	0 to 6V (203) 0 to 10V (403/603)	-
Phase Rotation	-	Yes (2 wire)
Auto AC/DC	Yes (V & A)	Yes (V & A)
Auto Power OFF	Yes	Yes
Hold Button	Yes	Yes
Backlight Button	Yes	Yes
Min/Max Button	Yes	Yes
True InRush® Function	Yes	Yes
Relative Function	Yes	Yes
Peak $\pm$ Function	-	Yes
Hz Button	Yes	Yes

*3-phase measurements assume balanced load



*Models 203 & 205 only

200 Series

400 & 600 Series
Housing Only

FEATURES

- 1000V CAT IV Rated (Models 403/603 & 405/605)
- UL 94 VI flame retardant self-extinguishing
- 10,000-count (400 & 600 Series) and 6000 count (200 Series) blue electroluminescent backlit display
- Measures up to 1000Vac (1400V peak), 1000Vdc and AC+DC with resolution to 10mV
- Measures up to 2000Aac and 3000Adc (model dependent)
- Measures single- and three-phase power (real, reactive and apparent) up to 3MW with resolution to 1W (model dependent)
- Measures W, VA, var and PF for single- and three-phase balanced systems (Models 205, 405 & 605)
- Measures frequency to 20kHz with 0.1Hz resolution
- Auto selects AC or DC measurement voltage
- True InRush® current measurement with 100mS capture
- Jaw opening up to 1.33" (34mm) (200 series), 1.89" (48mm) (400 series) and 2.36" (60mm) (600 series)
- K-thermocouple and adapter included (Models 203, 403 & 603)

CATALOG NO. DESCRIPTION

2139.12	Clamp-On Meter Model 203 (TRMS, 1000Vac/dc, 600Aac/900Adc, Ohms, Continuity, Temperature)
2139.40	Power Clamp-On Meter Model 205 (TRMS, 1000Vac/dc, 600Aac/900Adc, Ohms, Continuity, Phase Rotation, Power, THD)
2139.21	Clamp-On Meter Model 403 (TRMS, 1000Vac/dc, 1000Aac/1500Adc, Ohms, Continuity, Temperature)
2139.50	Power Clamp-On Meter Model 405 (TRMS, 1000Vac/dc, 1000Aac/1500Adc, Phase Rotation, Ohms, Continuity, Power, THD)
2139.31	Clamp-On Meter Model 603 (TRMS, 1000Vac/dc, 2000Aac/3000Adc, Ohms, Continuity, Temperature)
2139.60	Power Clamp-On Meter Model 605 (TRMS, 1000Vac/dc, 2000Aac/3000Adc, Phase Rotation, Ohms, Continuity, Power, THD)

