



## TMC6-HE Sensor

### Temperature (6") Sensor

A faster response version of our TMC6-HD complete with a plated copper sensor probe that can be mounted to a pipe or flat surface. The sensor is packaged with its own accessories for either strapping to a pipe or attaching to a flat surface. For use with HOBO U-Series, UX120-006M external-channel data loggers or ZW series wireless datanodes.

#### Parts Included:

Thermal grease is included for improved thermal conductivity. two tie wraps a screw



#### Supported Measurements:

Temperature

#### Key Advantages:

- Faster response time
- Suitable for pipe mounting
- Accessories included
- Can be plugged directly into the external input jacks of U12, UX120, or ZW Family loggers to expand the range of measurement options and applications.

## TMC6-HE Sensor Specifications

**Measurement range:** -40° to 100°C (-40° to 212°F)

**Accuracy:**

w/U12:  $\pm 0.25^{\circ}\text{C}$  from 0° to 50°C ( $\pm 0.45^{\circ}\text{F}$  from 32° to 122°F), insert probe 2.3 cm (0.9 inches) minimum;

w/ZW:  $\pm 0.21^{\circ}\text{C}$  from 0° to 50°C ( $\pm 0.38^{\circ}\text{F}$  from 32° to 122°F), insert probe 2.3 cm (0.9 inches) minimum;

w/UX120-006M:  $\pm 0.15^{\circ}\text{C}$  from 0° to 70°C ( $\pm 0.27^{\circ}\text{F}$  from 32° to 158°F), insert probe 2.3 cm (0.9 inches) minimum;

**Resolution:**

w/U12: 0.03° at 20°C (0.05° at 68°F);

w/ZW: 0.02°C at 25°C (0.04°F at 77°F);

w/UX120-006M: 0.002° at 25°C (0.003° at 77°F);

**Drift:** <0.1°C (<0.2°F) per year

**Response time in air:** 3 min. typical to 90% in air moving 1 m/sec (2.2 mph)

**Housing:** Copper-plated sensor tip

**Dimensions:** 0.9 x 5.8 cm (0.38 x 2.30 inches)

**Cable length:** 1.8m (6 feet)

**Weight:** 34 g (1.1 oz)